

**PARTNER**

CARE . TRUST . RESPONSIBILITY

# POS System PT-5910

## Cost Effective Touch Terminal



The new PT-5910 POS Terminal is developed for business owners looking for practical, cost effective POS solution. The PT-5910 uses latest ATOM technology to ensure a high processing performance for its users and it is equipped with the top rated and energy-efficient ATOM D525 CPU.

**Special Features:**

- Intel Atom CPU 1.8 GHz
- Low Cost of Ownership
- DDR3 2x SODIMM slots 1GB
- Supports up to 4GB of Memory
- Supports Dual Displays (15" or 11.6" screen)
- Spill-proof resistant design

**Optional:**

- 3-track MSR
- Customer display module (2 x 20 VFD)
- Biometric reader, Smart Card Reader, I-Button, RFID reader

## POS System PT-5910

### Technical data

<b>Item</b>	<b>PT-5910</b>	
<b>CPU Type</b>	Intel®Atom™ Processor D525 (1M Cache, 1.8 GHz Dual Core)	
<b>Chipset</b>	Intel®NM10 Express	
<b>LCD</b>	15" active color TFT-LCD, resolution 1024 x 768	
<b>Touch</b>	5-wire Resistive touch (PS2)	
<b>Memory</b>	DDR3 2x SODIMM slots 1GB (up to 4 GB)	
<b>LAN</b>	10/100/1000 Gigabit Ethernet	
<b>Storage</b>	Internal 3.5" type SATA HDD or Internal SATA SSD 8GB x 1 (When Wall-mounted)	
<b>I/O Interface</b>	3 x COM ports 1 x DB-15 VGA port 1 x DB-25 for LPT port 1 x PS/2 Keyboard port 1 x PS/2 Mouse port 1 x RJ11 port 1 x RJ-45 LAN port with activity/ link and speed LEDs 3 x audio ports (1 x Line-in, 1 x Line-out , 1 x MIC-in) 4 x USB 2.0 ports 1 x DC +12V power adaptor connector	
<b>Operation System</b>	Windows 7, Windows XP, Windows CE, Linux (ubuntu, Fedora), WEPOS, POSReady	
<b>Power Supply</b>	AC100~240V/DC12V, 7.5A, 90 watt power adaptor	
<b>Dimensions</b>	360 mm (W) x 246 mm (D) x 315 mm (H)	
<b>Environment</b>	<b>Operating</b>	<b>Storage</b>
	Temperature	0~45 °C      -20~60 °C
	Humidity	15% ~ 80%      15% ~ 80%
<b>Certification</b>	CE/FCC Class A, CCC, VCCI, LVD, KC	
<b>Options</b>	3-track MSR, Customer display module (2 x 20 VFD), Biometric Reader, Smart Card Reader, I-Button, RFID reader	



15-90 degrees tilt angle



Support Dual Display  
15" or 11.6"



Spill proof design



Support Pole mount Dual



Quick release latch design  
for easy maintenance



2 x 20 VFD Rear Display

