

PARTNER

CARE . TRUST . RESPONSIBILITY

All-in-One Touch POS Terminal PT-6210

All you need



The All-in-One Touch POS Terminal PT-6210 is a perfect solution for small and medium-size enterprises to keep pace with competitors. The POS Terminal comes with integrated customer display, 80mm Epson thermal printer and 3-track MSR as standard. Further components like Addimat/Dallas lock, RFID or 2nd screen can be built in as an option.

Its compact and small footprint design makes the device extremely counter-space saving. Furthermore the attractive and at the same time inconspicuously appearance fits into every POS environment. Without any extra modules, cables etc. it is easy to install and can be used in many different businesses like retail, kiosk, convenience-stores, fashion or hospitality.

Special Features:

- Elegant, compact and fanless design
- 10.4" TFT-LCD touch screen
- Open architecture
- Modular design for easy maintenance
- Integrated 3-track MSR
- 80 mm Epson thermal printer
- 2x20 VFD customer display

Optional:

- Solid State Drive
- RAID
- RFID module
- WiFi module

All-in-one POS Terminal PT-6210

Technical data

| Item | PT-6210 | |
|------------------------|---|------------------------|
| CPU | Intel Atom N270 @ 1.6GHz/512K L2 Cache | |
| Chipset | Intel 945GSE + ICH7M | |
| LCD | 10.4" TFT-LCD; Resolution: 800 x 600, 250cd/m ² | |
| Touch | 5-wire resistive touch | |
| Memory | System chips with DDR2 1GB std, support up to 2GB | |
| LAN | 10/100/1000Mbps on board Ethernet Controller | |
| Storage | IDE 3.5" HDD or optional SATA SSD | |
| I/O ports | 4 x COM ports 1 x RJ11 port (+24V) 1 x PS/2 Keyboard port 1 x RJ-45 LAN port 5 x USB ports 1 x DC +12V 1 x VGA port | |
| Operation System | WEPOS / POSReady / Windows XP Pro / Windows XP embedded / Windows 7 / Linux | |
| Power Supply | AC 100V~240V / DC12V / 15A 180 Watt power adapter | |
| Environment | Operating | Storage |
| | Temperature | 0~40 °C -20~60 °C |
| | Humidity | 15% ~ 80% 15% ~ 80% |
| Dimension | 328 mm (W) x 289,3 mm (D) x 246,8 mm (H) | |
| Integrated Peripherals | 3-track MSR, 2 x 20 VFD customer display, 80 mm Epson Thermal printer with auto cutter and Paper Feed | |
| Options | Solid State Drive, RAID, RFID module, WiFi module | |



10.4" TFT-LCD touch Screen



3-Track MSR



80mm Epson Thermal printer with Auto Cut and Paper Feed



Rear VFD Customer Display



Compact and small foot print



Modular design for easy maintenance

